

Digi-stick Soft Touch 35 Micron

- Bi-axially Oriented Polypropylene Film (BOPP)
- SOFT TOUCH finish
- Exclusive peach skin texture
- Enhances original colours of your print
- Outstanding surface adhesion for all types of coatings, inks, hot-melt and foils
- Superior bonding strength to all digital ink/toners
- Low melt thermal adhesive

Ever versatile and useable; this extensive range of Bi-axially Oriented Polypropylene Films (BOPP) include Corona pre-treated / coated and print receptive grades neatly paired with user friendly low-melt thermally activated adhesive.

Used daily by our customers on a range of products including luxury packaging, brochures, catalogues, book covers and jackets, labels and posters.

Specifications

BASE FILM	Polypropylene Film (BOPP)
SURFACE FINISH	Matt/Velvet
AVAILABLE STOCK WIDTHS	315, 440, 445, 450, 510, 630, 635, 710

Other widths available upon request

Typical Properties

PROPERTY		UNIT	TEST METHOD	VALUE
THICKNESS		(μm)		35
YIELD		m^2/kg In^2/Lb	Internal Test Method	31.15 21 903
WETTING TENSION	B	Dynes/cm	ASTM D 2578	46
C.O.F FILM/FILM	B/B		ASTM D1894	0.70
APPLICATION TEMPERATURE	A	$^{\circ}\text{C}$ $^{\circ}\text{F}$	Internal Test Method	110 – 130 230 – 260
LAMINATION STRENGTH	A	$\text{N}25.4/\text{mm}$ Lb/In	Internal Test method	≥ 7.5 ≥ 1.68
GLOSS	B	%	ASTM D 2457 45 $^{\circ}$	6

A: Adhesive Side B: Soft Touch Side

The above information is indicative only. The results shown are a general guide to the material properties which are subject to change and do not act as a guarantee.



01844 208308 info@gifproducts.co.uk www.gifproducts.co.uk

Graphic Image Films Ltd. Unit 5 Ridge Way • Crendon Industrial Park • Long Crendon • Buckinghamshire • HP18 9BF