

## FOILING – DIGITAL TONER FOILS

# Digital Toner/ Sleeking Foils 12 Micron

- Suitable for use on all toner types
- For unlaminated and laminated substrates
- Over printable
- No need for foil dies
- Thermally activated adhesive layer
- Easy to use

Easy to use range of Digital Toner/  
Sleeking Foils  
neatly paired with user friendly  
low-melt thermally activated  
adhesive

Used daily by our customers  
on a range of products including  
luxury packaging, brochures,  
catalogues, business cards  
and much more

## Specifications

BASE FILM	Polyester Film Liner (PET)
SURFACE FINISH	Available in Gold gloss, Silver gloss, Rose Gold, Black, Green, Blue and Clear gloss
AVAILABLE STOCK WIDTHS	320

## Typical Properties

PROPERTY	UNIT	TEST METHOD	VALUE
THICKNESS	( µm )		14
HEAT SHRINKAGE	MD	ASTM D1204 (150°C/30min)	2.5 +/- 0.5%
	TD		1.5 +/- 0.5%
Aluminium Metalised Layer	A	Optical Density (1.9-2.0)	400-450
Lamination Temperature	°C		90-110
Storage Conditions	°C		Min 5°C Max 30°C

The above information is indicative only.  
The results shown are a general guide to the material properties  
which are subject to change and do not act as a guarantee.



01844 208308 [info@gifproducts.co.uk](mailto:info@gifproducts.co.uk) [www.gifproducts.co.uk](http://www.gifproducts.co.uk)

Graphic Image Films Ltd. Unit 5 Ridge Way • Crendon Industrial Park • Long Crendon • Buckinghamshire • HP18 9BF