

Thermal Matt 22 Micron

- Bi-axially Oriented Polypropylene Film (BOPP)
- Natural matt finish
- Yellow tint free
- Food contact safe
- 2 Side corona treated
- UV/foil compatible
- Low Melt Thermal Adhesive

Ever versatile and useable; this extensive range of Bi-axially Oriented Polypropylene Films (BOPP) include Corona pre-treated / coated and print receptive grades neatly paired with user friendly low-melt thermally activated adhesive.

Used daily by our customers on a range of products including luxury packaging, brochures, catalogues, book covers and jackets, labels and posters.

Specifications

BASE FILM	Polypropylene Film (BOPP)
SURFACE FINISH	Matt
AVAILABLE STOCK WIDTHS	315, 440, 445, 450, 510, 610, 630, 635, 710, 890, 1010

Other widths available upon request

Typical Properties

PROPERTY		UNIT	TEST METHOD	VALUE
THICKNESS		(μm)		22
YIELD		m^2/kg In^2/Lb	Internal Test Method	51.8 36 419
AVERAGE SUBSTANCE		g/m^2		19.3
WETTING TENSION	A/B	Dynes/cm	ASTM D 2578	$\geq 40/40$
APPLICATION TEMPERATURE	A	$^{\circ}\text{C}$ $^{\circ}\text{F}$	ASTM D-1204	100 – 120 212 – 248
GLOSS	B	Gardiner	ASTM D2457 45 $^{\circ}$	58

A: Adhesive Side B: Matt Side

The above information is indicative only. The results shown are a general guide to the material properties which are subject to change and do not act as a guarantee.



01844 208308 info@gifproducts.co.uk www.gifproducts.co.uk